



IB03/03432

PCT/IB 03/03432

15.09.03



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 09 OCT 2003

WIPO PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

Signed

Dated

P. Mahoney
22 July 2003



Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

THE PATENT OFFICE

K

30 JUL 2002

NEWPORT

The Patent Office

Cardiff Road

Newport

Gwent NP9 1RH

1. Your reference PH/8151

30JUL02 E737073-3 002833

P01/7700 0.00-0217572.7

2. Patent application number

(The Patent Office will fill in this part)

0217572.7

13 JUL 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Nokia Corporation

Keilalahdentie 4, FIN-02150,
Espoo, Finland.

Patents ADP number (if you know it)

7652217001

If the applicant is a corporate body, give the country/state of its incorporation

Finland

4. Title of the invention

Portable Devices for Connection to the Person

5. Name of your agent (if you have one)

Swindell & Pearson

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

48 Friar Gate,
Derby DE1 1GY

Patents ADP number (if you know it)

00001578001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Yes

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form	0
Description	9 ✓
Claim(s)	6 ✓
Abstract	0
Drawing(s)	21 2 ✓

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

1 /

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature *Swindell & Pearson* Date 29/07/02
Swindell & Pearson

12. Name and daytime telephone number of person to contact in the United Kingdom Mr. P. Higgin - 01332 367051

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Portable Devices for Connection to the Person

5 The present invention relates to portable devices for connection to the person. In particular, it seeks to reduce the desirability of such devices to thieves.

10 The portable nature of mobile phones mean that they are easily misplaced and stolen. It would be desirable to make a telephone less desirable to a thief and, in particular, less likely to be stolen if misplaced or left behind.

15 A current trend in the mobile telephone industry, is the miniaturisation of telephones. Another trend is that mobile telephones are becoming fashion accessories and are often visibly worn on or about the person. For example, mobile telephones may be hung around the neck, around the wrist or attached to a belt or clothing. One problem with wearing telephones in this way is that they can be grabbed by a thief.

20 It would be desirable to reduce the likelihood of such a theft taking place and also to reduce the risk of personal injury during such a theft.

25 According to one aspect of the present invention there is provided a portable device comprising: unauthorised separation detection means arranged to detect the unauthorised separation of the portable device from a counterpart; and control means arranged to effect at least partial disablement of one of the portable device and the counterpart in response to the unauthorised separation of the portable device and counterpart. The control means may be arranged to effect at least partial disablement of the use of a cellular radio transceiver housed in one of the portable device and the counterpart.

30 According to one embodiment, the counterpart is a person and the control means are arranged to effect at least partial disablement of the portable device (and the cellular radio transceiver housed therein). According to another

embodiment the counterpart is a counterpart device and the portable device and the counterpart device are arranged to form a couple between each other and the control means are arranged to effect at least partial disablement of the portable device (and the cellular radio transceiver housed therein). According to

5 another embodiment, the counterpart is a counterpart device and the portable device and the counterpart device are arranged to form a couple between each other and the control means are arranged to effect at least partial disablement of the counterpart device (and the cellular radio transceiver housed therein).

10 According to another aspect of the invention there is provided a portable device having a radio transmitter, comprising: a releasable connector arranged to connect the portable device to a person and arranged to release the connection of the portable device to the person if the device is grabbed while connected to the person; and control means arranged to effect at least partial
15 disablement of the device in response to the release of the releasable connector.

The partial disablement of the device results in the device not being capable of normal use but only being capable of restricted use or no use.

20 The releasable connector may be anything which allows the device to be worn by a person, for example, a neck strap, a wrist strap or a clip. With a neck strap the portable device is connected to a person by being supported around their neck. With a wrist strap the portable device is connected to a person by being attached to their wrist. With a clip the portable device is connected to a
25 person by being attached to their clothing or accessories. The releasable attachment releases the connection by breaking, coming apart or otherwise losing the connection.

The portable device may comprise a sensor for sensing the release of the
30 connector. The sensor may sense a change in electrical characteristics of the connector such as its resistance.

The portable device may be a mobile cellular telephone in which the radio transmitter is the transmitting portion of the telephone's radio

transceiver. The partial disablement of the telephone results in the telephone not being capable of normal use. For example, the telephone may be capable of making only emergency calls and incapable of receiving calls (restricted use) or incapable of making and receiving any calls (no use). The partial disablement of the mobile cellular device may allow the device to make calls to a network operator call centre and/or re-direct restricted calls to/from the device to a network operator call centre.

Preferably, the portable device can be re-enabled following authentication e.g. by the user calling the network operator call centre, possibly using the partially disabled mobile cellular device, and providing password authentication.

The portable device is preferably arranged to allow the operation of the releasable connector to be activated/deactivated. In the activated state, the control means is able to effect at least partial disablement of the device in response to the release of the releasable connector.

The control means is preferably arranged to control the radio transmitter to send a message in response to the release of the releasable connector.

In an embodiment where the device is or comprises a cellular mobile telephone for operation in a cellular communications network, the control means may be arranged to effect at least partial disablement of the device by controlling the radio transmitter to send a disabling message to the network for disabling normal operation of the telephone in the network. The mobile telephone may comprise a handset and a replaceable card, which enables the handset to operate as a telephone in the network, and the network may be responsive to the disabling message sent by the mobile telephone to disable the card from normal use in the network and/or to disable the handset from normal use in the network.

The disablement of the card will preferably involve an adaptation to one or more databases used in the network for controlling user access to the

network. The disablement of the card may completely prevent the card from enabling the normal operation of any handset as a telephone in the network.

The disablement of the handset will preferably involve an adaptation to
5 one or more databases used in the network for controlling equipment access to the network. The handset, even when disabled, may still be capable of making emergency calls e.g. to 911 (USA) or 999 (GB).

In an embodiment where the device is or comprises a cellular mobile
10 telephone for operation in a cellular communications network and the telephone comprises a handset and a replaceable card, which enables the handset to operate as a telephone in the network, the control means may be arranged to effect at least partial disablement of the device by locking the handset to the card, in response to the release of the releasable connector, so
15 that it can be used normally as a telephone only in conjunction with the card present in the handset when the telephone is grabbed. If a different card is used with the handset after locking, the telephone may still be capable of making emergency calls e.g. to 911, but will not be capable of placing calls to user determined telephone numbers. Preferably, the control means, in response to
20 the release of the releasable connector, is additionally arranged to send a disabling message to the network for disabling the card. The disablement of the card may completely prevent the card from enabling the normal operation of any handset as a telephone in the network.

25 According to another aspect of the invention there is provided a cellular mobile telephone, for operation in a cellular communications network, comprising: a releasable connector arranged to connect the mobile telephone to a person and arranged to release the connection of the mobile telephone to the person if the device is grabbed while connected to the person; and control
30 means arranged to send a disabling message to the network in response to the release of the releasable connector.

For a better understanding of the present invention reference will now be made by way of example only to the accompanying drawings, in which:

Fig. 1 is a schematic illustration of the functional components of a GSM mobile telephone embodiment of the present invention;

5 Fig. 2 illustrates the exterior of the GSM telephone embodiment; and

Fig. 3 illustrates a GSM cellular communications network embodiment.

10 Fig. 1 is a schematic illustration of the functional components of cellular mobile telephone 2 for operation in a cellular communications network, which in this example is a GSM network. The telephone 2 comprises a handset 4 and a SIM card 6. The handset 4 comprises a controller 10, radio transceiver circuitry 12 electrically connected to the controller 10, a user input keypad 14 electrically connected to the controller 10, a user input microphone 16 electrically connected to the controller 10, a loud speaker 18, for audio output to the user, electrically connected to the controller 10, and a display 20 electrically connected to the controller 10. These components are standard components of a GSM mobile telephone handset. The person skilled in the art will readily understand how they inter-operate to send and receive messages such as SMS messages and to make and receive telephone calls. The handset 4, further comprises, a sensor 22 electrically connected to the controller 10 and a connector 24 connected to the sensor 22.

25 Fig. 2 schematically illustrates the exterior of the handset 4. In this embodiment, the connector 24 comprises a strap 26 and a couple 28. The strap 26 is connected to the body of the handset 4 via the couple 28. The strap 26 may be suitable for being passed over the head of a user so that the handset 4 hangs from the neck or it may be suitable for being passed over the hand and tightened around the wrist so that the handset 4 hangs from the wrist. Although a strap 26 is illustrated in this figure, it should be appreciated that different connectors 24 could be used. For example, the connector 24 could in an alternative embodiment be a clip for attaching the handset 4 to a belt or to clothing.

The connector 24 which connects the telephone to a person is designed so that it will release the connection when the telephone 2, attached to a person, is grabbed by a thief. For example, in the embodiment of Fig. 2 the strap 26 may have an inherent weakness so that when the telephone 2 is grabbed the strap breaks. Alternatively, the couple 28 may be designed to sever the connection between the strap 26 and the telephone 2 when the telephone is grabbed by a thief. The sensor 22, illustrated in Fig. 1, is arranged to sense when the telephone 2, which is attached to a person, has been grabbed by a thief. This is preferably done by sensing when the connector 24 ceases to connect the telephone 2 to the person. This may be achieved by, for example, forming a closed conductive path from the telephone 2 through the couple 28 and around the strap 26 to return to the telephone 2 while the telephone 2 is attached to the person. The severance of this closed conductive path, when the connector releases its connection, is easily detectable using known techniques such as by periodically testing the conductive path for changes in resistance.

Alternatively, the sensor 22 may not be physically connected to the connector 24. Instead, the sensor 22 comprises a low power radio transceiver or infrared transmitter for communicating with a counterpart device carried by the person. The low power radio transceiver in the sensor 22 may for example communicate with a low power radio transceiver in the wrist watch of the user of the phone. When the link between the telephone 2 and the counterpart device is broken because the telephone and counterpart device have been separated the sensor 22 is activated. The sensor 22 is therefore acting as a proximity detector and is activated when the telephone 2 and the counterpart device are separated beyond the threshold distance. A separation beyond the threshold distance would occur, for example, if the telephone 2 were stolen by a thief or inadvertently left behind. In this alternative embodiment, the activation of the sensor causes the controller 10 to at least partially disable the telephone 2. This may occur, for example, by the radio transceiver 12 of the mobile telephone transmitting a disable message and/or, by the locking of the SIM card 6 to the handset 4. As a variation, to this alternative embodiment the sensor 22 may be positioned in the counterpart as opposed to the telephone 2. The controller 10 is connected to a low power radio frequency transceiver which

communicates with a low power radio frequency transceiver connected to the sensor 22 in the counterpart. The sensor 22 operates as a proximity detector, detecting when the separation between the counterpart and the telephone exceeds a threshold. This may be done by, for example, measuring the attenuation of a signal. When the separation exceeds the threshold, the sensor 22 in the counterpart is activated and sends a command to the controller 10 which causes the at least partial disablement of the mobile telephone 2.

In response to the activation of the sensor 22 the controller 10 when in an active mode effects at least a partial disablement of the telephone 2. This disablement may be achieved in a number of different ways. However, when the controller is in an inactive mode it does not respond to activation of the sensor. The user can select whether the controller 10 is in the active or inactive mode.

According to a preferred embodiment, the controller 10 controls the radio transceiver 12 to send a disabling message which will substantially prevent the telephone 2 being used as a normal telephone. The telephone 2 may be completely prevented from operating in the cellular network or it may, for example, be capable of only performing a very limited number of functions for example making emergency calls only, or calling only a network operator call centre.

Figure 3 illustrates a GSM cellular network 40 comprising a plurality of cells 42 each with a base station 44. The mobile telephone 2 communicates in the network by transmitting to and receiving from the serving base station 44 of the cell 42 in which it is located. As the mobile station moves from one cell to another the serving base station 44 changes. The base stations 44 are controlled by a mobile switching centre (MSC) 46. The MSC 46 controls the routing of communications from sender to receiver. The MSC 46 is connected to the Home Location Register (HLR) 48. This is a central database storing all the information that allows a user to access and use the network 40. The HLR 48 stores the International Mobile Subscriber Identity (IMSI) for each user of the network 40 and a restriction class for each user which indicates whether a user

is able to transmit and receive communications and the type of communications that are possible. The network 40 may also have an Equipment Identity Register (EIR) 50 connected to the MSC 46. The EIR 50 is a database which tracks handsets. The EIR, if present, may blacklist a stolen handset via its International Mobile Equipment Identity (IMEI) thereby preventing its use in the network 40.

In response to activation of the sensor 22, the controller 10 controls the radio transceiver 12 to send a disabling SMS message which will substantially prevent the telephone 2 being used as a normal telephone. The message may be sent immediately, or when the phone is next activated. The phone may self-activate in response to activation of the sensor. The message sent to the network may include the International mobile subscriber identity (IMSI) stored in the SIM 6 and the International mobile equipment identity (IMEI) stored in the handset 2. The IMSI uniquely identifies the user in the network and the IMEI uniquely identifies the handset. Alternatively, if the telephone is already participating in the network and has a temporary mobile subscriber identity (TMSI), the message may include the TMSI. The network is therefore capable, having received the message, of uniquely identifying the handset 4 and the SIM card 6 either directly from the IMEI and IMSI or indirectly via the TMSI. The network is then able to change the restriction class in the HLR 48 for that IMSI and is capable of registering the handset having that IMEI as stolen in the EIR 40. Thus the handset will not be capable of being used, except possibly to make emergency calls to 911/999 or calls to the network operator call centre and the SIM card will not be capable of being used in another telephone. Preferably, the disabled telephone can be re-enabled by the network operator, after receiving a password during a call, possibly placed using the partially disabled telephone, to the network operator call centre.

According to another embodiment of the invention, the controller 10 responds to the sensor 22 sensing that the connector 24 has been released, by locking the handset 4 to the particular SIM card 6 which is connected to it at that time. This locking procedure is described in the SIM personalisation procedure described in GSM 02.22 and in EP-B-0301740. The controller 10 may

also control the radio transmitter 12 to send a disabling SMS message to the network 40. This disabling message may be the same and operate in the same manner as described in the preceding paragraph. Alternatively, if the EIR 50 is not present in the network 40, the message may change the restriction class in the HLR 48 for that IMSI. The locking procedure may be reversed by entering a secret PIN code to the telephone or remotely by the network operator after receiving a password. The effect of the disable message may be reversed by the network operator after receiving a password as described in the preceding paragraph.

10

Although the preceding paragraphs have described an embodiment of the invention with reference to a GSM cellular communication network and a GSM compliant mobile telephone, it should be appreciated that the invention has application in other cellular communication networks and telephones, and in other appliances with radio transmitters. It should therefore be appreciated that modifications and variations to the examples given can be made without departing from the scope of the invention as claimed.

Whilst endeavouring in the foregoing specification to draw attention to those features of the invention believed to be of particular importance it should be understood that the Applicant claims protection in respect of any patentable feature or combination of features hereinbefore referred to and/or shown in the drawings whether or not particular emphasis has been placed thereon.

CLAIMS

1. A portable device comprising:

5 unauthorised separation detection means arranged to detect the unauthorised separation of the portable device from a counterpart; and

control means arranged to effect at least partial disablement of one of the portable device and the counterpart in response to the unauthorised separation of the portable device and counterpart.

10 2. A portable device as claimed in claim 1, wherein the control means are arranged to effect at least partial disablement of the use of a cellular radio transceiver in one of the portable device and the counterpart

15 3. A portable device as claimed in claim 1 or 2, wherein the counterpart is a person and the control means are arranged to effect at least partial disablement of the portable device.

20 4. A portable device as claimed in claim 3, wherein the unauthorised separation detection means are a proximity detector that detects the proximity of the portable device and the person.

25 5. A portable device as claimed in claim 3 or 4, wherein the unauthorised separation detection means are means for detecting the release of a releasable connector connecting the portable device to the person.

6. A portable device as claimed in any one of claims 2 to 5, wherein the portable device comprises a cellular radio transceiver.

30 7. A portable device as claimed in claim 1 or 2, wherein the counterpart is a counterpart device and the portable device and the counterpart device are arranged to form a couple between each other and the control means are arranged to effect at least partial disablement of the portable device.

8. A portable device as claimed in claim 7 wherein the couple between the counterpart device and the portable device is via electrical connection or wireless connection.

5 9. A portable device as claimed in claim 7 or 8 wherein the unauthorised separation detection means is arranged to detect the absence of the couple between the portable device and the counterpart device.

10 10. A portable device as claimed in claim 9 wherein the couple is lost on the release of a releasable connector connecting the portable device to a person carrying the counterpart device.

11. A portable device as claimed in any one of claims 7 to 10, wherein the portable device comprises a cellular radio transceiver.

15

12. A portable device as claimed in claim 1 or 2, wherein the counterpart is a counterpart device and the portable device and the counterpart device are arranged to form a couple between each other and the control means are arranged to effect at least partial disablement of the counterpart device.

20

13. A portable device as claimed in claim 12 wherein the couple between the counterpart device and the portable device is via electrical connection or wireless connection.

25 14. A portable device as claimed in claim 12 or 13 wherein the unauthorised separation detection means is arranged to detect the absence of the couple between the portable device and the counterpart device.

30 15. A portable device as claimed in claim 14 wherein the couple is lost on the release of a releasable connector connecting the portable device to a person carrying the counterpart device.

16. A portable device as claimed in any one of claims 12 to 15, wherein the counterpart device comprises a cellular radio transceiver.

17. A portable device as claimed in claim 6 or 11, wherein the control means is arranged to effect at least partial disablement of the portable device by controlling the cellular radio transceiver to transmit a disable message.

5

18. A portable device as claimed in claim 1 or 2 wherein the portable device is or comprises a cellular mobile telephone for operation in a cellular communications network and the control means is arranged to effect at least partial disablement of the portable device by sending a disabling message to the
10 network for disabling normal operation of the telephone in the network.

19. A cellular telephone network comprising a portable device as claimed in claim 18 wherein the mobile telephone comprises a handset and a replaceable card, which enables the handset to operate as a telephone in the network, and
15 the network is responsive to the disabling message sent by the mobile telephone to disable the card from normal use in the network and/or to disable the handset from normal use in the network.

20. A portable device as claimed in claim 1 or 2 wherein the device is or
20 comprises a cellular mobile telephone for operation in a cellular communications network and the telephone comprises a handset and a replaceable card, which enables the handset to operate as a telephone in the network, wherein the control means is arranged to effect at least partial disablement of the portable device by locking the handset to the card so that
25 the handset can be used normally as a telephone only in conjunction with the card which is present in the handset at the time of locking.

21. An arrangement comprising a portable device and a counterpart, the arrangement having a radio transmitter and comprising:

30 unauthorised separation detection means arranged to detect the unauthorised separation of the device from the counterpart; and

control means arranged to effect at least partial disablement of the device and/or counterpart in response to the unauthorised separation of the device and counterpart.

22. A portable device having a radio transmitter, comprising:

a releasable connector arranged to connect the portable device to a person and arranged to release the connection of the portable device to the person if the device is grabbed while connected to the person; and

control means arranged to effect at least partial disablement of the device in response to the release of the releasable connector.

23. A portable device as claimed in claim 22 wherein the control means is arranged to control the radio transmitter to send a message in response to the release of the releasable connector.

24. A portable device as claimed in claim 22 wherein the device is or comprises a cellular mobile telephone for operation in a cellular communications network and the control means is arranged to control the radio transmitter to send a disabling message to the network for disabling normal operation of the telephone in the network.

25. A cellular telephone network comprising a portable device as claimed in claim 3 wherein the mobile telephone comprises a handset and a replaceable card, which enables the handset to operate as a telephone in the network, and the network is responsive to the disabling message sent by the mobile telephone to disable the card from normal use in the network and/or to disable the handset from normal use in the network.

26. A device as claimed in claim 22 wherein the device is or comprises a cellular mobile telephone for operation in a cellular communications network and the telephone comprises a handset and a replaceable card, which enables the handset to operate as a telephone in the network, wherein the control means is arranged to lock the handset to the card, in response to the release of the releasable connector, so that the handset can be used normally as a telephone only in conjunction with the card which is present in the handset when the telephone is grabbed.

27. A device as claimed in claim 26 wherein the control means is additionally arranged to send a disabling message to the network for disabling the card so that it can no longer enable a handset to operate normally as a telephone in the network.

5

28. A cellular telephone network comprising a device as claimed in claim 27 wherein the network is responsive to the disabling message sent by the mobile telephone to disable the card from normal use in the network.

10 29. A cellular mobile telephone, for operation in a cellular communications network, comprising:

a releasable connector arranged to connect the mobile telephone to a person and arranged to release the connection of the mobile telephone to the person if the device is grabbed while connected to the person; and

15 control means arranged to send a disabling message to the network in response to the release of the releasable connector.

30. A cellular telephone network comprising a mobile telephone as claimed in claim 29 wherein the mobile telephone comprises a handset and a
20 replaceable card, which enables the handset to operate as a telephone in the network, and the network is responsive to the disabling message sent by the mobile telephone to disable the card from normal use in the network and/or to disable the handset from normal use in the network.

25 31. A cellular mobile telephone comprising a mobile telephone as claimed in claim 29 comprising a handset and a replaceable card, which enables the handset to operate as a telephone in the network, wherein the control means is arranged to lock the handset to the card, in response to the release of the releasable connector, so that the handset can be used normally as a telephone
30 only in conjunction with the card which is present in the handset when the telephone is grabbed.

32. A cellular telephone network comprising a mobile telephone as claimed in claim 31 wherein the network is responsive to the disabling message sent by

the mobile telephone to disable the card from normal use in the network.

33. A portable device substantially as hereinbefore described with reference to and/or as shown in the Figures.

5

34. A mobile telephone substantially as hereinbefore described with reference to and/or as shown in the Figures.

10

35. A cellular radio communications network substantially as hereinbefore described with reference to and/or as shown in the Figures.

36. A portable device having a radio transmitter, comprising:

unauthorised removal means arranged to detect the unauthorised removal of the device from a person porting the device; and

15

control means arranged to effect at least partial disablement of the device in response to the unauthorised removal of the device.




Fig 1




Fig 2




Fig 3